

Spies Hecker® VOC Compliance Chart

Jefferson County, Kentucky
Regulation 7.79 - Standards of Performance for Commercial Motor Vehicle and Mobile Equipment Refinishing Operations
Group 2 Vehicles: See footer below
Effective: 4/2/1994



Description		Compliant Rules			Applied VOC lbs/gal	Remarks	
Surface Preparation VOC Limit = 1.7 lbs/gal (204 g/L)							
	107™ Axalta Low VOC Gun & Equipment Cleaner				0.2		
	2110™ Axalta Silicone Remover Water				1.4		
	220™ Axalta Silicone Remover Low VOC				0.2		
	265™ Axalta Plastic Cleaning Paste				0.1		
	Permady® Plastic Cleaning Paste 7081				0.1		
	Permady® Silicone Remover 7085				1.6		
	Permady® Silicone Remover 7086				1.4		
	Permady® Silicone Remover 7096				0.2		
Jefferson County, Kentucky							
Description	Mix Ratio	Hardener	Reducer/ Additive	Addtl Product	Max Applied VOC (LE) lbs/gal	Remarks	
Pretreatment VOC Limit = 6.5 lbs/gal (780 g/L)							
	+50%	N/A	8580, 3363, 3365	N/A	6.5		
	Prima® Primer 3255 (Aerosol)	N/A	N/A	N/A	N/A		
	Prima® Wash Primer 4075	1:1	4076	N/A	N/A	6.5	
	420™ Axalta Etch Primer	1:1	421	N/A	N/A	6.5	
	110A™ Axalta 1K Primer Surfacar Light Gray	Ready to Use	N/A	N/A	N/A	N/A	
	1200A™ Axalta 1K Primer Surfacar Dark Gray	Ready to Use	N/A	N/A	N/A	N/A	
	195™ Axalta Metal Pretreatment Wipes	Ready to Use	N/A	N/A	N/A	6.5	
	Prima® 1K Primer Surfacar 4085 (Aerosol)	Ready to Use	N/A	N/A	N/A	N/A	
	Prima® 1K Primer Surfacar 4085	+50%	N/A	8580, 3363, 3365	N/A	6.5	
	Axalta® Pretreatment Wipes PS4000™	Ready to Use	N/A	N/A	N/A	6.5	
Primers/Primer-Surfacers VOC Limit = 2.8 lbs/gal (340 g/L)							
	Permady® 1K Productive Primer Surfacar 4100	+5-10%	N/A	6000	N/A	2.8	
	Permasol® EP Primer Surfacar 4502	2:1+0-10%	4503	3394	N/A	2.8	
	460A™ Axalta Epoxy 2K	Ready to Use	included	N/A	N/A	N/A	Aerosol
	Permacron® VHS Surfacar 5150	1.5:1+0-5%	3192, 3194, 3196	3392, 3394	N/A	2.8	
	Permacron® VHS Surfacar 5150	2:1+10-20%	3170	3369, 3370, 3371	N/A	2.8	
	Permasol® 2:1 Surfacar 5155	4:1+20-30%	3193, 3195, 3197, 3199	3369, 3370, 3371	N/A	2.8	
	Permasol® 2:1 Surfacar 5155 Elasticized	2:1+20-30%	3193, 3195, 3197, 3199	3369, 3370, 3371	+30% 9050	2.8	9050 must be added before hardener.
	Permasol® 2:1 Surfacar 5157	5:1+10-20%	3192, 3194, 3196	3392, 3392, 3394, 5409, 5410	N/A	2.8	
	Permasol® 2:1 Surfacar 5157 Elasticized	4:1+10-20%	3192, 3194, 3196	3392, 3392, 3394, 5409, 5410	+15% 9050	2.8	9050 must be added before hardener.
	Permasol® 1K UV Starlight Primer Surfacar 9002 (Aerosol)	Ready to Use	N/A	N/A	N/A	N/A	Aerosol
	Permasol® 1K UV Starlight Primer Surfacar 9002	Ready to Use	N/A	N/A	N/A	2.8	Non-Aerosol version
Primer-Sealers VOC Limit = 3.5 lbs/gal (420 g/L)							
	Permasol® 2:1 Surfacar 5155	2:1+30%	3193, 3195, 3197, 3199	9070	+10-20% 3369, 3370, 3371	3.5	
	Permasol® 2:1 Surfacar 5155 Elasticized	2:1+30%	3193, 3195, 3197, 3199	9070	+10-20% 3369, 3370, 3371	3.5	
	Permasol® Spectro Surfacar 5400	2:1+20-30%	3193, 3195, 3197, 3199	9070	+15-30% 9050	3.5	
	Permasol® Spectro Surfacar 5400 Elasticized	2:1+20-30%	3193, 3195, 3197, 3199	9070	+30% 9050	3.5	9050 must be added before hardener.
	Permasol® Spectro Sealer 5450	4:1+30%	3192, 3194, 3196	5409, 5410	N/A	3.5	
	Permasol® Spectro Sealer 5450 Elasticized	3:1+30%	3192, 3194, 3196	5409, 5410	+15-30% 9050	3.5	9050 must be added before hardener.
	Permady® 2K Sealer 5650	1:5%	3080	N/A	N/A	3.5	
Single Stage Topcoats VOC Limit = 5.2 lbs/gal (630 g/L)							
	Permacron® Acrylic Urethane Series 257	3:1+5-10%	3307, 3309, 3310, 3315, 3320, 3325	8580, 3363, 3365	N/A	5.2	
	Permacron® Automotive Topcoat Series 257 FP-1004 Rally Matt Black	4:1+25%	3220, 3230, 3240, 3245	8580, 3363, 3365	+15% 9050	5.2	
	Permacron® Automotive Topcoat 257 Series FP-1002 Blue Black	4:1+25%	3220, 3230, 3240, 3245	8580, 3363, 3365	+15% 9050	5.2	
	Permacron® Automotive Top Coat FP 1005 Warm Gray VV604N	3:1	3307, 3309, 3310, 3315, 3320, 3325	N/A	+0-5% 8092, 8096	5.2	
	Permacron® Automotive Top Coat FP 1005 Warm Gray VV604N	4:1+10%	3220, 3230, 3240, 3245	8580, 3363, 3365, 3394, 5409, 5410	+0-5% 8092, 8096	5.2	
Multi-stage Topcoat VOC Limit = 3.5 lbs/gal (420 g/L) applied as a system							
Basecoats: Must be used with specific clearcoats for compliance							
	Permady® Hi-TEC Base Coat	+10-30%	N/A	6050, 6051, 6052, 6053	N/A	3.5	
	Permady® Hi-TEC Base Coat w/ Hardeners	+5-10% +10-30%	3080	6050, 6051, 6052, 6053	N/A	3.5	
	Permady® Base Coat Series 280/285	+0-15%	N/A	6000	N/A	3.5	
	Permady® Base Coat Series 280/285	+0-10%	N/A	6002	N/A	3.5	
	Permady® Base Coat Series 280/285	+5-10%	6007	+10-20% 6000 or 0-10% 6002	N/A	3.5	
	Permasol® 2K Diamond Midcoat, MC 0001	2:1+10-15%	3192, 3194, 3196	3392, 3394	+15% 9050	3.5	
	Permasol® 2K Transparent Red Midcoat, MC 0002	2:1+10-15%	3192, 3194, 3196	3392, 3394	+15% 9050	3.5	
	Permasol® 2K Transparent Blue Midcoat, MC 0003	2:1+10-15%	3192, 3194, 3196	3392, 3394	+15% 9050	3.5	
	Permacron® Transparent Midcoat 9100	1:1+3%	3194, 3196	3394	9045, 9049, 9056, 9057, 9058	3.5	
Clearcoats: Must be used as a system with specified basecoats							
	Permasol® Air Dry Clear Coat 8094	4:1+20%	3192, 3194, 3196	3392, 3394	N/A	3.5	
	Permasol® Air Dry Clear Coat 8094 Elasticized	4:1+20%	3192, 3194, 3196	3392, 3394	+10% 9050	3.5	9050 must be added before hardener.
	Permasol® Low VOC Clear Coat 8096	2:1+10-15%	3192, 3194, 3196	3392, 3394	N/A	3.5	
	Permasol® Low VOC Clear Coat 8096 Elasticized	2:1+10-15%	3192, 3194, 3196	3392, 3394	+15% 9050	3.5	9050 must be added before hardener.
	Permasol® Low VOC Clear Coat 8098	2:1+5%	3192, 3194, 3196	3392, 3394	N/A	3.5	
	Permasol® Low VOC Clear Coat 8098 Elasticized	2:1+10%	3192, 3194, 3196	3392, 3394	+15% 9050	3.5	9050 must be added before hardener.
	Permasol® Low VOC Clear Coat 8098 w/ 9055	See TDS 8098	3192, 3194, 3196	3392, 3392, 3394	N/A	3.5	
	Permasol® Low VOC Clear Coat 8098 w/ 8092 Matte Clear Coat Additive	See TDS 8092	3192, 3194, 3196	3392, 3394	N/A	3.5	
Specialty Coatings VOC Limit = 7.0 lbs/gal (840 g/L) - Shall not exceed 10% of all coatings applied on a weekly basis.							
Adhesion Promoters							
	Permacron® Transparent Surfacar 8550	3:1+20-30%	3307, 3309, 3310, 3315, 3320, 3325	8580, 3363, 3365	N/A	7.0	
	Permacron® Transparent Surfacar 8550	4:1+ 35%	3220, 3230, 3240, 3245	8580, 3363, 3365	N/A	7.0	
	Permasol® Vario Surfacar 8590	3:1+20-30%	3307, 3309, 3310, 3315, 3320, 3325	8580, 3363, 3365	N/A	7.0	
	Permasol® Vario Surfacar 8590	5:1+30-40%	3220, 3230, 3240, 3245	8580, 3363, 3365	N/A	7.0	
Elastomeric Coatings							
	Permacron® 1:1 Elastic Primer Surfacar 3300	1:1	3301	N/A	N/A	7.0	
	Prima® Elastic Primer 3304	Ready to Use	N/A	N/A	N/A	7.0	
	Prima® Elastic Primer 3304 (Aerosol)	Ready to Use	N/A	N/A	N/A	N/A	
	Prima® Elastic Primer 4190	Ready to Use	N/A	N/A	N/A	7.0	
	320™ Axalta Plastic Polyolefin Adhesion Promoter	Ready to Use	N/A	N/A	N/A	N/A	
	325™ Axalta Plastic Polyolefin Adhesion Promoter	Ready to Use	N/A	N/A	N/A	7.0	
	110A™ Axalta Plastic Polyolefin Adhesion Promoter Aerosol	Ready to Use	N/A	N/A	N/A	N/A	
	320™ Axalta Plastic Primer Surfacar Black	1:1	331	N/A	N/A	7.0	
	330™ Axalta Plastic Primer Surfacar Gray	1:1	331	N/A	N/A	7.0	
	Permacron® Matt System Clear Coat 8165 / Permacron® Semi-Gloss System Clear Coat 8170	See Matt Clear System TDS	3225, 3240	3365	N/A	7.0	
	Permasol® Mating Component MA110 / Permacron® Semi-Gloss System Clear Coat 8170	See Matt Clear System TDS	3225, 3240	3365	N/A	7.0	
	Permasol® Matte Clear Coat Additive 8092 with 8035	See TDS 8092 for Mixing Recommendations				7.0	
	Permacron® Semi-gloss Elastic Clear Coat 8070	3:1+5-10%	3307, 3309, 3310, 3315, 3320, 3325	8580, 3363, 3365	N/A	7.0	
	Permacron® Semi-gloss Elastic Clear Coat 8070	4:1+20%	3220, 3230, 3240, 3245	8580, 3363, 3365	N/A	7.0	
	Permacron® FP1004 Rally Matte Black	3:1+5-10%	3307, 3309, 3310, 3315, 3320, 3325	8580, 3363, 3365	N/A	7.0	
Fisheye Eliminator							
	Permacron® Antislicone 8510	25ml:1 w/RTS 2k Clear Coat	N/A	N/A	N/A	7.0	
Uniform Finish Coatings							
	Permacron® Speed Blender 1036	4:1 w/Permacron® or Permasol® Clear Coats (RTS)				7.0	
	1:2 w/293/295 RTS					7.0	
	Permady® Blend-in Additive 9005	1:1 w/Permady® Base Coat Series 280/285 (RTS)				7.0	
	Permady® Blend-in Additive 9017	1:2 w/Permady® Base Coat Series 280/285 (RTS)				7.0	
	Permady® Blend-in Additive 9017	+50%	N/A	9016	N/A	7.0	
	Permady® Hi-TEC Blend-in Additive 1050 or 1051	+10%	N/A	6050, 6052	N/A	7.0	
	Permady® Hi-TEC Blend-in Additive 1050	+5%	N/A	1053	N/A	7.0	
	750™ Axalta Blender (Aerosol)	Ready to Use	N/A	N/A	N/A	N/A	
Other Products							
	Permasol® Additive Maroon 9056	See 998.0 TDS for compliant mixing recommendations				5.0	
	Permasol® Additive Magenta 9057	See 998.0 TDS for compliant mixing recommendations				5.0	
	Permasol® Additive Violet 9058	See 998.0 TDS for compliant mixing recommendations				5.0	
	Permasol® Additive Deep Red 9049	See 998.0 TDS for compliant mixing recommendations				5.0	
	Permasol® Additive Blue 9045	See 998.0 TDS for compliant mixing recommendations				5.0	
	Permady® Sanding Paste 1120	Ready to Use	N/A	N/A	N/A		
	Raderall® Spray Polyester 3508	+5%	9520	+5% 7690 or +2.5% 9010	N/A		
	766A™ Axalta 1K Trim Black Satin	Ready to Use	N/A	N/A	N/A	N/A	Aerosol
	Axalta E-Coat Restore Aerosol	Ready to Use	N/A	N/A	N/A		See TDS for compliance and usage instructions.
	Permacron® Fine Putty 7715	Ready to Use	N/A	N/A	N/A		

Group 2 Vehicles: Buses and mobile equipment

For complete product usage and mixing recommendations, see the product specific technical data sheet located on www.spieshecker.com/USA.
Copyright © 2025 Axalta Coating Systems. Spies Hecker® and all products designated with TM or ® are trademarks or registered trademarks of Axalta Coating Systems for its brands of refinish systems. All rights reserved.