

Standex® VOC Compliance Chart

Group 1 Vehicles : Cars, large-heavy duty trucks, light/medium duty trucks, vans, and motorcycles
El Dorado County AQMD Rule 230 - Effective 06/01/1995



Description	Article #	Compliant Rules				Applied VOC g/L	Remarks
Surface Preparation VOC Limit = 0.6 lbs/gal (72 g/L)							
Standoflex® Low VOC Plastic Cleaner	16010	El Dorado				21	
Axalta® 107™ Low VOC Gun & Equipment Cleaner	107					25	
Axalta® 220™ Silicone Remover Low VOC	220					20	
Axalta® 130™ Cleaner	130					0	
Axalta® 265™ Plastic Cleaning Paste	265					1	
Standohyd® VOC Cleaner 25	16178					25	
Surface Preparation (Plastic Parts Only) VOC Limit = 6.5 lbs/gal (780 g/L)							
Axalta® 200™ Silicone Remover Slow	200	El Dorado				780	Plastic Parts Only
Standohyd® Cleaner	16176					188	
Standox® Silicone Remover Antistatic	16203					773	
Description	Article #	Mix Ratio	Hardener	Thinner/ Additive	Addtl Product	Max Applied VOC (LE) g/L	Remarks
Pretreatment VOC Limit = 6.5 lbs/gal (780 g/L)							
	400A	1:1	N/A	N/A	N/A	N/A	
	410A	Ready to Use	N/A	N/A	N/A	N/A	
	420	1:1	421	N/A	N/A	780	
	495	Ready to Use	N/A	N/A	N/A	780	
	14696	Ready to Use	N/A	N/A	N/A	N/A	
	16134	+50%	N/A	2K Thinners	N/A	780	
	16167	1:1	16168	N/A	N/A	780	
	16189	2:1	16190	N/A	N/A	780	
	16141/16228	Ready to Use	N/A	N/A	N/A	N/A	
	PS4000™	Ready to Use	N/A	N/A	N/A	780	
Primers/Primer-Surfacers VOC Limit = 2.1 lbs/gal (250 g/L)							
	460A	Ready to Use	N/A	N/A	N/A	N/A	
	16220/16221	5:1+10-20%	PF Hardeners	16215, 16224, 16225	N/A	250	
	16220/16221	5:1 +10-20%	PF Hardeners	16215, 16224, 16225	+15% 15260	250	15260 must be added before hardener.
	16231	1 +5-15%	N/A	80188		250	
Primer-Sealers VOC Limit = 3.5 lbs/gal (420 g/L)							
	16222/16223	4:1+30%	PF Hardeners	16224, 16225	N/A	420	
	16222/16223	4:1+30%	PF Hardeners	16224, 16225	+15% 15260	420	15260 must be added before hardener.
	16181	Ready to Use	N/A	N/A	N/A	N/A	
Single Stage Topcoats VOC Limit = 5.0 lbs/gal (600 g/L)							
	16604	3:1+5%	PF Hardeners	16215, 16224, 16225	+0-5% 16230, 16211	600	
Multistage Topcoat VOC Limit = 4.5 lbs/gal (540 g/L) applied as a 2-stage or 3-stage coating system							
Basecoats: Must be used with specific clearcoats for compliance							
	See Price List	10-30%	N/A	19301, 19302, 19303	N/A	540	
	See Price List	+0-10% +10-30%	17400	19301, 19302, 19304	N/A	540	
	See Price List	+50%	N/A	MSB Thinners	N/A	540	
	See Price List	+15%+30-40%	2.1 Hardeners	MSB Thinners	N/A	540	
	14017	+15%+40%	2.1 Hardeners	MSB Thinners	N/A	540	
	16240	See TDS 9911	PF Hardeners	16215	+15% 15260	540	15260 must be added before hardener.
	16241	See TDS 9911	PF Hardeners	16215	+15% 15260	540	15260 must be added before hardener.
	16242	See TDS 9911	PF Hardeners	16215	+15% 15260	540	15260 must be added before hardener.
Clearcoats: Must be used as a system with basecoats at/under 4.5 lbs/gal (540 g/L) for compliance							
	14580	2:1+0-5%	2.1 Hardeners	2.1 Thinners	N/A	540	Not compliant if used in a 3-stage coating system with Standox Basecoat.
	14580	2:1+0-5%	2.1 Hardeners	2.1 Thinners	+15-30% 15260	540	Not compliant if used in a 3-stage coating system with Standox Basecoat. 15260 must be added before hardener.
	16161	2:1	2.1 Hardeners	N/A	N/A	540	Not compliant is used in a 3-stage coating system with Standox Basecoat.
	16211/16217	2:1+15%	PF Hardeners	16215	N/A	540	
	16211/16217	2:1+15%	PF Hardeners	16215	+10-15% 15260	540	15260 must be added before hardener.
	16216	2:1+5%	PF Hardeners	16215	N/A	540	
	16216	2:1+10%	PF Hardeners	16215	+10-15% 15260	540	15260 must be added before hardener.
	16218	4:1 +20%	PF Hardeners	16215	N/A	540	
	16218	4:1 +20%	PF Hardeners	16215	+10% 15260	540	15260 must be added before hardener.
	See MIX 607 TDS (9572 & 9572.1)		PF Hardener PFH 30-35	PF Thinner	N/A	540	Refer to TDS for mixing instructions over both metal and plastic.
	See MIX 607 TDS (9572.1)		PF Hardeners	PF Thinner	N/A	540	Refer to TDS for mixing instructions over both metal and plastic.
	See MIX 607 TDS (9572.1)		PF Hardeners	PF Thinner	N/A	540	Refer to TDS for mixing instructions over both metal and plastic.
Specialty Coatings VOC Limit = 7.0 lbs/gal (840 g/L)							
Elastomeric Coatings							
	11816/16192	1:1	11824	N/A	N/A	840	
	12065	Ready to Use	N/A	N/A	N/A	840	
	16202/16227	Ready to Use	N/A	N/A	N/A	840	
	16232/16233	4:1+15%	PF Hardeners	16224	+15% 16234	840	
	See Matt Clear System TDS		16187, 16162	11484	N/A	7.0	
	See Matt Clear System TDS		16187, 16162	11484	N/A	7.0	
	16205	4:1+10%	16162	16206	N/A	7.0	75:25, 70:30, or 80:20 with Standox® 2K HS Clear (14580)
	10887	3:1+0-10%	2.1 Hardeners	2K Thinners	+ 15% 15260	840	15260 must be added before hardener.
	14408	Aerosol	N/A	N/A	N/A	N/A	
Uniform Finish Coatings							
	16150	Ready to Use	N/A	or +10% MSB Thinners	N/A	840	
	16150	1:2 w/Standox® Basecoat (RTS)				840	
	16150	15%	2.1 or 2K Hardeners	N/A	N/A	840	
	19310/19311	+5-10%	N/A	19301, 19302, 19303	+5% 18316	840	
	19310/19311	+0-5%	N/A	18316	N/A	840	
	19310	4:1+20-30%	19310	19301, 19302, 19303	N/A	840	
	19310	4:1+20-30%	19310	19301, 19302, 19304	N/A	840	
	19310	1:1+10%	19310	Mix 199	N/A	840	
	11247	3:1 w/RTS 2K Clear				840	
	16174	4:1 w/2K Clear (RTS)				840	
	16174	See TDS 1206 for compliant mixing recommendations				840	
	16174	See TDS 1206 for compliant mixing recommendations				840	
Other Products - Consult technical data sheet for usage and compliance.							
	766A™	Ready to Use	N/A	N/A	N/A		
	See Price List	Ready to Use	N/A	N/A	N/A		
	715™	Ready to Use	N/A	N/A	N/A		
	16255	See TDS 9913	N/A	N/A	N/A	540	
	16256	See TDS 9913	N/A	N/A	N/A	540	
	16257	See TDS 9913	N/A	N/A	N/A	540	
	16679	See TDS 9913	N/A	N/A	N/A	540	
	KA684	See TDS 9913	N/A	N/A	N/A	540	
	14670	see TDS	N/A	N/A	N/A		